



FEATURES

Automatic hand dryer with sensor operation. Engineered to suit washrooms requiring low noise levels. Streamlined, minimal design for smaller environments. Durable steel casing with theft resistant torx screws. Tamper-proof & safe intake opening. Pivot bracket inside cover for ease of installation.

INSTALLATION OPTIONS

Electrical connection by cord & plug (as supplied). Can be direct wired by an electrician.

SPECIFICATION

- Electrical Supply: AC, 220-240V, 50/60Hz, 4.16A
- Motor: 100 Watt, 2800 RPM, dual ball bearings
- Element: 900 Watt, protected by thermal cut-out
- Air Speed: 12m/s
- Noise Level: 67±2 dB-A
- Weight: Gross 4.6kg, Shipping 5.2kg
- Certificate of Suitability No: GMA-500004
- Electrical Safety Requirement: AS/NZS 60335.2.23:2004
- Protection Category: IPX1

FINISH

Satin Stainless Steel cover. Charcoal polycarbonate grill.

RECOMMENDED INSTALLATION HEIGHT


Men's washroom	1270mm
Women's washroom	1194mm
Children's washroom ages 14-15	1194mm
Children's washroom ages 11-13	1092mm
Children's washroom ages 8-10	991mm
Children's washroom ages 4-7	889mm
Disabled person's washroom	1016mm

WARRANTY

One year.

Applause Satin Stainless Steel shall be Model No. HDAPSSS as manufactured by ASI JD MacDonald.

All ASI JD MacDonald accessible compliant products when installed must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.



Please use installation template supplied with product before commencing installation

