



#### FEATURES

State of the art, ergonomic and high speed. Air blows down from vents on top, preventing water splashback and achieving fast drying time. Ultra hygienic Super Filter System eliminates 99% of airborne bacteria. Water is pushed back onto an absorbent and continuously evaporating ceramic plate. Water not evaporated or absorbed is channelled into a drip tray (not the floor). Can only be removed using a dual step security system offering enhanced vandal resistance.

#### INSTALLATION OPTIONS

Electrical connection by cord & plug (as supplied). Can be direct wired by an electrician.


#### SPECIFICATION

- Electrical Supply: AC, 220-240V 50/60Hz, 1600W
- Motor: 1 HP Brush Type, Dual Ball Bearings
- RPM: 11,000 – 19,000 (adjustable)
- Element: 400 - 900 Watt (adjustable)
- Air Volume: 55 – 88 CFM (89 – 124m<sup>3</sup>/h) (adjustable)
- Noise Level: 65 – 69.8 dB
- Weight: 10.8kg, Shipping 12.8kg
- Drying Time: Approx 12 seconds
- Certificate of Suitability No: GMA-500003
- Electrical Safety Requirements: AS/NZS 60335.2.23:2004
- Protection Category: IPX1

#### FINISH

White ABS


#### RECOMMENDED INSTALLATION HEIGHT (Above Finished Floor from top of hand drying chamber)

Men's washroom	1150mm
Women's washroom	1080mm
Children's washroom ages 4-7	780mm
Children's washroom ages 8-10	880mm
Children's washroom ages 11-13	965mm
Children's washroom ages 14-16	1080mm
Accessible Compliant washroom	900mm 

#### WARRANTY

5 years.

**Tri-Umph White** shall be Model No. 10-20201-2 as manufactured by ASI JD Macdonald.

 All ASI JD Macdonald disabled compliant products, when installed, must be in accordance with AS1428 to ensure the specified product is complying with all washroom specification requirements.

