



### Materials & Features

Constructed from heavy duty DR brass with a polished chrome finish and an above bench solenoid for ease of maintenance, the Formatta sensor tap is suitable for public washrooms, offices, schools, shopping centres, stadiums, airports & accessible installations. The sensor detects the presence of the user's hand(s) in the field directly in front of the sensor in the water stream - this activates the flow of water until the hands are removed from the field.

### Technical Detail

Inlet Connection:	15mm BSP (1/2")
Flow Time:	On demand
Max. Flow Time:	60 seconds
Flow Rate:	5L per minute
Water Pressure:	150 – 500 kPa
Water Supply:	Single temp (Max 50°C)
Electrical Supply:	Mains power
Sensor:	IR (avoid highly reflective surfaces/direct light)

### Installation

RBA1211-600 requires a bench cut out of Ø28-32mm with a maximum bench thickness of 38mm. A mains power GPO should also be provided by others.

### Related Products

- B824** Automatic Soap Dispenser
- RBA1083-Series** 'Inox' Self Closing Push Button Tap
- B7128** Trimline Sensor Operated Hand Dryer

**Important:** Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

