



Materials & Features

Self-closing tap is designed for public washrooms, offices, schools, shopping centres, stadiums, airports & accessible installations. Single connection, tap will deliver cold or pre mixed water, single temperature only. Tap is activated by pushing/pulling the lever, flow will cease when preset time is achieved. Tap cartridge is self-cleaning. Black plastic cover on handle for safety and luminance contrast.

Technical Detail

Tap Body:	DZR Brass, Chrome plated
Inlet Connection:	15mm BSP (1/2")
Flow Time:	4-10 seconds (non-adjustable)
Operating Pressure:	200 – 500 kPa
Supply:	Single temp (Max. 55°C)
Flow Rate:	4.5L / 8L per minute
Locknut:	Brass
Force to activate:	9N @ 400 kPa

Available Models

RBA1015-600	6 Star [4.5Lpm] Self Closing Lever Tap
RBA1015-400	4 Star [8.0Lpm] Self Closing Lever Tap

Related Products

RBA1083-999-010	Heavy Duty Brass Locknut (add-on for installations in vandal prone areas)
RBA8867-100	'Benefit' Accessible Stainless Steel Basin
RBA8889-182	'Curvalinear' Accessible Stainless Steel Basin

Important: Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

