



### Materials & Features

Self-closing tap is designed for public washrooms, offices, schools, shopping centres, stadiums, airports & accessible installations. Single connection, tap will deliver cold or pre mixed water, single temperature only. Tap is activated by pushing/pulling the lever, flow will cease when preset time is achieved. Tap cartridge is self-cleaning. Black plastic cover on handle for safety and luminance contrast.

### Technical Detail

Tap Body:	DZR Brass, Chrome plated
Inlet Connection:	15mm BSP (1/2")
Flow Time:	4-10 seconds (non-adjustable)
Operating Pressure:	200 – 500 kPa
Supply:	Single temp (Max. 55°C)
Flow Rate:	4.5L / 8L per minute
Locknut:	Brass
Force to activate:	9N @ 400 kPa

### Available Models

<b>RBA1015-600</b>	6 Star [4.5Lpm] Self Closing Lever Tap
<b>RBA1015-400</b>	4 Star [8.0Lpm] Self Closing Lever Tap

### Related Products

<b>RBA1083-999-010</b>	Heavy Duty Brass Locknut (add-on for installations in vandal prone areas)
<b>RBA8867-100</b>	'Benefit' Accessible Stainless Steel Basin
<b>RBA8889-182</b>	'Curvalinear' Accessible Stainless Steel Basin

**Important:** Installation instructions and current rough-in details should be furnished with each fixture. Do not rough in without certified dimensions. Dimensions are subject to manufacturer's tolerance of +/-10mm.

